



MELISSA HARTMANN



Strength & agility on 4 wheels.

Built on our popular MP-250 base, the more powerful MT-290 is equal parts modern workhorse and mobile workshop. Its efficient AC motor offers impressive acceleration, even when towing loads of 10,000 lbs. Its all-steel construction and four-wheel vibration dampening design ensure a smooth and stable ride even on bumpy surfaces. This agile, round-the-clock tow tractor effortlessly maneuvers through challenging areas, including doorways. A multipurpose tugger boasting a long-lasting industrial battery with easy under-the-seat access. EE rating available.

Personnel Carriers, Tow Tractors Other Models: 48V, 24V Narrow















LOAD CAPACITY 700 lbs




TOWING CAPACITY 10,000 lbs



SPEED MPH 8 mph



TURNING RADIUS




FEATURES

High-efficiency asynchronous AC / Direct Drive motor Robust long-life industrial batteries AC controller with sealed connectors paired with multifunction display Powerful automatic electromagnetic parking brake Battery-saving efficient DC/DC converter







Dimensions

VEHICLE		
Height	44"	1,118 mm
Length	78"	1,981 mm
Width	38"	965 mm
Wheel Base	52"	1,321 mm
Ground Clearance	n/a	n/a
DECK		
Height	25"	635 mm
Width	38"	965 mm
Length	21"	533 mm
UNIT WEIGHT		
With Batteries	n/a	n/a
Without Batteries	n/a	n/a
BATTERIES		
Height	17,5	17,5
Length	16"	406 mm
Width	35,2	35,2
Weight - Min	n/a	n/a
Weight - Max	n/a	n/a

Performances

VEHICLE

Passengers	1	
Load Capacity	700 lbs	318 kg
Tow Capacity	10,000 lbs	4,536 kg
Drawbar Pull - Normal	n/a	n/a
Drawbar Pull - Ultimate	n/a	n/a
Speed MPH	8 mph	13 km/h
Turning Radius	77"	1,956 mm

Specifications and standard equipment are subject to change without notice.

Specifications

POWERTRAIN

Motor	Brushless AC motor, 7.5 HP Intermittent, 10 HI Max
Controller	AC Electronic speed controller
Drive Axle	Helical gear differential
Brakes	Rear hydraulic drum brakes, regenerative braking
Wheels	4.8x8 LRC pneumatic tires
Transmission	Direct drive
Suspension	Dual leaf springs on rear
Starter	n/a
Clutch	n/a
Engine	n/a
ENERGY	
	36 Volt
Voltage	30 VUIL
Voltage Battery	No battery included
J	
Battery Charger	No battery included
Battery Charger	No battery included No charger included
Charger Alternator	No battery included No charger included n/a

OPERATOR COMPARTMENT

Color

Lights

Steering	Automotive steering wheel
Seats	Bucket seat on slide adjusters
Indicators	Multifunction display including speedometer, battery state of charge, hour meter, odometer and fault warnings. Password-protected parameters and monitoring capability.
Safety	Reverse alarm, deadman seat switch, horn
Accessories	36V/12V converter for 12-volt accessories, bolt- on front bumper

Security orange or federal yellow

LED headlight & tail/brake light

Standards

Conforms to requirements for type E, UL 583, ANSI B56.9





Cabs & Top Covers

290-CAB02 Steel cab and doors, wiper, rearview mirror **Hitches** Clevis type hitch (1") with safety spring" 448-056 Hand release lever for clevis hitch 280-RELEASE01 Lights Headlights on key switch 240-024K **Performances** Factory programmed to 6 mph max. speed 280-PROGRAMMING04 **Safety Features** 360-023 Motion beeper Pole mounted strobe light, amber 240-025 Wheels Flat prevention tire treatment 260-075 Solid softy rubber wheels 260-WHEELS06

The list above shows the most popular options for this vehicle. More options are available. To learn more about the MT - 290 - 36V HD options, please contact your representative. Options, specifications and standard equipment are subject to change without notice.





Melissa Hartmann Marketing Team **Atlas Companies**

mhartmann@AtlasLift.com

www.motrec.com