

MELISSA HARTMANN APRIL 8, 2021







Stylish and extremely powerful.


The MT-440 is the latest generation of heavy-duty tow tractors. Behind its stylish, compact design is a highly efficientdirect-drive powertrain, plenty of power to haul 30,000-lb. loads over long distances, and an oversized industrial battery to lengthen running time. Features like tight turning radius, rear battery positioning and shock-dampening suspension deliver exceptional maneuverability, stability and comfort. This highly robust, low-maintenance twoseater is built to last—from bolt-on bumper to bumper. EE rating available.




Tow Tractors Other Models : IC, 48V Narrow, 48V









Dimensions

VEHICLE

Height	49"	1,245 mm
Length	100"	2,540 mm
Width	44"	1,118 mm
Wheel Base	53"	1,346 mm
Ground Clearance	n/a	n/a
DECK		
Height	n/a	n/a
Width	n/a	n/a
Length	n/a	n/a
UNIT WEIGHT		
With Batteries	n/a	n/a
Without Batteries	1,800 lbs	816 kg
BATTERIES		
Height	26.6"	676 mm
Length	27"	686 mm
Width	42.8"	1,086 mm
Weight - Min	2,800 lbs	1,270 kg
*	3,200 lbs	-

Performances

VEHICLE		
Passengers	2	
Load Capacity	500 lbs	227 kg
Tow Capacity	30,000 lbs	13,608 kg
Drawbar Pull - Normal	700 lbs	3,114 N
Drawbar Pull - Ultimate	1,900 lbs	8,452 N
Speed MPH	7 mph	11 km/h
Turning Radius	119"	3,023 mm

Vehicle shown may have optional accessories and is provided for illustrative purposes only.

Specifications and standard equipment are subject to change without notice.

Specifications

POWERTRAIN

Motor	25 hp Fan cooled shunt motor		
Controller	Electronic speed controller		
Drive Axle	Differential with automotive ring gear		
Brakes	Four-wheel hydraulic brakes, 11", regenerative braking		
Wheels	18x6x8 Solid Soft Rubber Wheels		
Transmission	Goodyear Eagle Synchronous drive		
Suspension	Front leaf spring suspension with dual shock absorbers, rear leaf spring suspension		
Starter	n/a		
Clutch	n/a		
Engine	n/a		
ENERGY			
Voltage	80 Volt		
Battery	No battery included		
Charger	No charger included		
Alternator	n/a		
Fuel	n/a		
CHASSIS			
Body	All-steel unibody construction		
Color	Security orange or federal yellow		
Lights	LED dual headlights & tail/brake lights		

OPERATOR COMPARTMENT

Steering	Power steering
Seats	Two bucket seats on slide adjusters
Indicators	Battery status indicator
Safety	Reverse alarm, deadman seat switch
Accessories	80V/12V converter for 12-volt accessories, horn

Standards

Conforms to requirements for type E, UL 583, ANSI B56.9



Cabs & Top Covers	
448-041	Steel cab and doors, wiper, rearview mirror
Equipments	
330-055F	ABC fire extinguisher
Hitches	
448-056	Clevis type hitch (1") with safety spring"
448HD-052	Hand release for clevis hitch (requires clevis hitch)
Safety Features	
360-023	Motion beeper
360-026	Pole mounted strobe light
Seats	
360-049	Seat belts, retractable, two passengers
Steering Systems	
448HD-100	Tilt-telescopic steering column

The list above shows the most popular options for this vehicle. More options are available. To learn more about the MT - 440 - 80V options, please contact your representative. Options, specifications and standard equipment are subject to change without notice.



Melissa Hartmann Marketing Team



Atlas Companies