




MELISSA HARTMANN APRIL 8, 2021




The ultimate long-load workhorse.


The MC-660 is the ideal carrier for long and heavy loads of up to 6,000 lbs.—even over long distances. Its fully customizable modular design features a low, long flatbed cargo deck and powerful four-wheel drive. Also available in unlimited configurations including our cab option, or with the single seat and half-cowl for full-length deck space on the right side. A rugged, multi-purpose vehicle offering safe and dependable performance, even when handling the heaviest loads.














Dimensions

VEHICLE		
Height	53"	1,346 mm
Length	130"	3,302 mm
Width	54"	1,372 mm
Wheel Base	77"	1,956 mm
Ground Clearance	n/a	n/a
DECK		
Height	23"	584 mm
Width	54"	1,372 mm
Length	78"	1,981 mm
UNIT WEIGHT		
With Batteries	n/a	n/a
Without Batteries	n/a	n/a
BATTERIES		
Height	n/a	n/a
Length	n/a	n/a
Width	n/a	n/a
Weight - Min	n/a	n/a
Weight - Max	n/a	n/a

Performances

VEHICLE

Passengers	2	
Load Capacity	3,500 lbs	1,588 kg
Tow Capacity	6,000 lbs	2,722 kg
Drawbar Pull - Normal	n/a	n/a
Drawbar Pull - Ultimate	n/a	n/a
Speed MPH	15 mph	24 km/h
Turning Radius	150"	3,810 mm

Vehicle shown may have optional accessories and is provided for illustrative purposes only.

Specifications and standard equipment are subject to change without notice.

Specifications

POWERTRAIN

Motor n/a
Controller n/a
Drive Axle Dual hydraulic wheel motors

Brakes 4-wheel hydraulic discs brakes, hand lever

parking brake

Wheels 5.7x8 LRB pneumatic tires
Transmission Hydrostatic pump

Suspension Front and rear leaf spring with shock absorber

suspensions

Starter 12-V positive engaging starter Clutch Automatic, automotive control

Engine Kohler V-twin cylinders, fan-cooled, 4-cycle gas

engine

ENERGY

Voltage n/a
Battery n/a
Charger n/a

Alternator 25 amp flywheel alternator

Fuel Unleaded regular gas only, 7 U.S. gallon tank

capacity

CHASSIS

Body 12-G plate steel, 2x4 tubular frame
Color Security orange or federal yellow
Lights LED dual headlights & tail/brake lights

OPERATOR COMPARTMENT

Steering Automotive steering wheel
Seats Two bucket seats on slide adjusters

Indicators Fuel gauge

Safety Seat switch, neutral start switch, oil sentry,

automatic engine shut down, reverse alarm

Accessories Horn, reverse alarm, neutral start switch

Standards

Conforms to UL 558 and ANSI B56.8





With unlimited configurations, we make customization quick, easy and affordable.

Cabs	& To	p Co	vers
------	------	------	------

G660-041	Steel cab & doors, wiper, rearview mirror, sound insulation
Decks	
G660-081	96" deck length"
Hitches	
360-086	Clevis type hitch with safety spring
Performances	
G660-08548	7,000 lbs capacity (includes solid rubber wheels, 8mph programming and 48" wide deck). Not available with 54" W deck
Safety Features	
660-026	Pole mounted strobe light
Seats	
G660-049	Seat belts, retractable, two passengers
Wheels	
660-074	Solid soft rubber wheels

The list above shows the most popular options for this vehicle. More options are available. To learn more about the MC - 660 - IC options, please contact your representative. Options, specifications and standard equipment are subject to change without notice.





Melissa Hartmann Marketing Team **Atlas Companies**

mhartmann@AtlasLift.com