

VEHICLE OVERVIEW

MELISSA HARTMANN



A versatile work tool with unlimited configurations.

The MP-240 is an economic and cost-effective vehicle that can adapt to any industry. It"s narrow and maneuverable enough to fit through door openings, but tough enough to withstand years of abuse. It'll move you and your stock three times faster than on foot, quickly boosting operational productivity. Features include underseat battery compartment, low-step entry, and front and lateral protection bars. Optional lift-out battery box and fold-down back seat. A multi-purpose vehicle offering great value and day-to-day reliability.

Personnel Carriers Other Models: 36V













PASSENGERS



LOAD CAPACITY 500 lbs



TOWING CAPACITY 2,000 lbs




7 mph





TURNING RADIUS

FEATURES

Reinforced bolt-on front and rear bumpers Time-saving lift-out battery compartment Fatigue- and accident-saving ergonomic suspension Built-to-last all-steel unibody construction Heavy-duty powder paint & protection







Dimensions

VEHICLE				
Height	40"	1,016 mm		
Length	78"	1,981 mm		
Width	30"	762 mm		
Wheel Base	50"	1,270 mm		
Ground Clearance	7"	178 mm		
DECK				
Height	25"	635 mm		
Width	30"	762 mm		
Length	20"	508 mm		
UNIT WEIGHT				
With Batteries	800 lbs	363 kg		
Without Batteries	480 lbs	218 kg		
BATTERIES				
Height	n/a	n/a		
Length	n/a	n/a		
Width	n/a	n/a		
Weight - Min	n/a	n/a		
Weight - Max	n/a	n/a		

Performances

VEHICLE

Passengers	1	
Load Capacity	500 lbs	227 kg
Tow Capacity	2,000 lbs	907 kg
Drawbar Pull - Normal	100 lbs	445 N
Drawbar Pull - Ultimate	400 lbs	1,779 N
Speed MPH	7 mph	11 km/h
Turning Radius	71"	1,803 mm

 $\label{thm:continuous} \textit{Vehicle shown may have optional accessories and is provided for illustrative purposes only.}$

Specifications and standard equipment are subject to change without notice.

Specifications

POWERTRAIN

Motor	6 hp shunt motor	
Controller	SEPEX Electronic speed controller	
Drive Axle	Helical gear differential	
Brakes	Dual self-adjusting mechanical drum brakes o rear, hand lever parking brake, regenerative braking	
Wheels	4.8x8 LRC pneumatic tires	
Transmission	Direct drive	
Suspension	Dual coil springs & shock absorbers on front, dual coil springs and shock absorber on rear	
Starter	n/a	
Clutch	n/a	
Engine	n/a	
ENERGY		
Voltage	24 Volt	
Battery	Four 6V-225AH batteries	
Charger	High-frequency (85-265VAC / 45-65Hz, 1kw), built-in and automatic.	
Alternator	n/a	
Fuel	n/a	
CHASSIS		
Body	14-G diamond-plate steel body, tubular frame, powder coating.	

OPERATOR COMPARTMENT

Color

Lights

Steering	Handlebar
Seats	Bucket seat on slide adjusters
Indicators	Battery status indicator
Safety	Reverse alarm, Deadman foot switch, Horn
Accessories	Bolt-on bumpers and rear wheel guards, 24V accessories to equalize cells and extend battery life.

Security orange or federal yellow LED headlight & tail/brake light

Standards

Conforms to requirements for type E, UL 583, ANSI B56.9





Batteries & Chargers	
240-001	260 AH batteries to replace four batteries
Driver Area Options	
240-020	Digital battery gauge with hour meter
Hitches	
240-057	Rear bumper with integrated clevis hitch (5/8") and safety spring"
Lights	
240-024K	Headlights on key switch
Performances	
242-031	Factory programmed to 6 mph max. speed
Safety Features	
240-025	Pole mounted strobe light, amber
Seats	
242-045	Convertible backrest, bench type seat, 8" rear step"
Steering Systems	
240-041	Automotive steering wheel
Wheels	
240-075	Flat prevention tire treatment
242-073 242-021	Solid softy rubber wheels Static strap
	·

The list above shows the most popular options for this vehicle. More options are available. To learn more about the MP - 240 - 24V options, please contact your representative. Options, specifications and standard equipment are subject to change without notice.





Melissa Hartmann Marketing Team **Atlas Companies**