

VEHICLE OVERVIEW

MELISSA HARTMANN APRIL 8, 2021




A genuine industrial vehicle / golf cart alternative.


This multi-purpose, multi-passenger vehicle is specifically designed to perform in rugged applications. It can efficiently carry personnel and cargo, climb hills, and tow up to 2,000 lbs.—simultaneously. With its bolt-on bumpers, high-strength tubular frame, and 14-G diamond-plate steel body, this work horse is built to last. Its modular design includes an optional four passenger configuration with foldaway rear seat. A safe, low-cost, low-maintenance utility truck that also makes a great golf cart alternative.




Personnel Carriers Other Models: 36V









Dimensions

VEHICLE			
Height	46"	1,168 mm	
Length	99"	2,515 mm	
Width	44"	1,118 mm	
Wheel Base	68"	1,727 mm	
Ground Clearance	n/a	n/a	
DECK			
Height	26"	660 mm	
Width	44"	1,118 mm	
Length	32"	813 mm	
UNIT WEIGHT			
With Batteries	n/a	n/a	
Without Batteries	n/a	n/a	
BATTERIES			
Height	n/a	n/a	
Length	n/a	n/a	
Width	n/a	n/a	
Weight - Min	n/a	n/a	
Weight - Max	n/a	n/a	

Performances

VEHICLE

Passengers	2	
Load Capacity	1,200 lbs	544 kg
Tow Capacity	2,000 lbs	907 kg
Drawbar Pull - Normal	n/a	n/a
Drawbar Pull - Ultimate	n/a	n/a
Speed MPH	15 mph	24 km/h
Turning Radius	127"	3,226 mm

 $\label{thm:constraints} \textit{Vehicle shown may have optional accessories and is provided for illustrative purposes only.}$

Specifications and standard equipment are subject to change without notice.

Specifications

POWERTRAIN

POWERIKAIN	
Motor	16 hp gas engine
Controller	n/a
Drive Axle	Helical gear differential
Brakes	Hydraulic, rear drums brake, hand lever parking brake
Wheels	5.7x8 LRC pneumatic tires
Transmission	CVT belt drive, F/N/R helical gears
Suspension	Front and rear leaf spring with shock absorber suspensions
Starter	12-V positive engaging starter
Clutch	Automatic centrifugal engagement
Engine	V-twin cylinders, fan-cooled, 4-cycle gas engine
ENERGY	
Voltage	n/a
Battery	n/a
Charger	n/a
Alternator	16 amp flywheel alternator
Fuel	Unleaded regular gas only, 7 U.S. gallon tank capacity

CHASSIS

Body	14-G diamond-plate steel body, tubular frame
Color	Security orange or federal yellow
Lights	LED dual headlights & tail/brake lights

OPERATOR COMPARTMENT

Steering	Automotive steering wheel
Seats	Two bucket seats on slide adjusters
Indicators	Fuel gauge
Safety	Seat switch, neutral start switch, oil sentry, automatic engine shut down, reverse alarm, horn
Accessories	Bolt-on Front & Rear Bumper, 4-Hole Hitch Plate, 12V accessories

Standards

Conforms to UL 558 and ANSI B56.8





Body Options	
TBD-17	3" longer operator compartment"
Cabs & Top Covers	
300-041	Steel cab and doors, wiper, rearview mirror
Decks	
300-053	Rear cargo box with 9" high solid metal sides with end gate"
Hitches	
360-086	Clevis type hitch with safety spring
Lights	
300-024	Turn signals with 4-way flashers
Safety Features	
360-026	Pole mounted strobe light
Seats	
300-051	Rear flip-up seat, (2 pass. additional seating), 9" side rail"
300-049	Seat belts, retractable, two passengers
Wheels	
260-073	4.8x8 solid softy on split rims

The list above shows the most popular options for this vehicle. More options are available. To learn more about the MP - 300 - IC options, please contact your representative. Options, specifications and standard equipment are subject to change without notice.





Melissa Hartmann Marketing Team **Atlas Companies**