

WWW ATI ASTOYOTA COM

# CONTACT US TODAY!




## **FEATURES & BENEFITS**

- Hard chrome-plated ram & piston
- · Self-lubricating bearings at all pivot points
- · Large steer wheels with "ball-thrust" steering
- Grease fittings
- Full adjustable push rods on forks
- 230° pivot action maneuvers in compact areas
- Only 1 snap ring 4 pins to remove hydraulic unit
- Tapered fork ends and maintenance-free skids for easy entry and exit of pallets
- Safety designed loop handle, includes neutral position, and fingertip release

#### WARRANTY

Atlas warrants this equipment when used under normal operating conditions excluding acid and alkali environments, to be of proper materials and first class workmanship. We agree to exchange, excluding labor, any defective moving parts (bearings and wheels, and hydraulic parts not including the chassis) returned to us by prepaid freight within 12 months from date of shipment.





### **SPECIFICATIONS**

Load Capacity	5,500 lbs.
Lowered Height of Forks	2.9 "
Raised Height	7 ¾"
Overall Width Across Forks	27"
Fork Width	6.3"
Space Between Forks	14.4"
Standard Fork Length	48"
Load Wheels	2.375" x 3.625"
Front Wheels (Steer) - Polyurethane	6.875" x 2"
Body Length (Including Pump)	16"
Load Roller Axle to Fork-Tip End of Fork:	
- Roller Down	6 ¾"
- Roller Up	9 ¾"
Approximate Weight	175 lbs.



SELF RETURN SPRING-A-MATIC HANDLE



HIGH TENSILE STEEL FRAME



EASY, QUIET TRAVEL

## **ABOUT THE UNIT**

Designed for use in food, chemical or pharmaceutical industries. Based on our best selling pallet truck, available in stainless steel or galvanized finish.